

## ➤ Zerust® ActivPowder™ (LS)-10F


The Zerust®/Excor® ActivPowder™(LS)-10F is a VCI (Volatile Corrosion Inhibitor) powder designed to protect metal surfaces in large voids from corrosion. This self-fogging powder combines VCI protection with a Flash Corrosion Inhibitor (FCI™) to protect against flash rust and provide long-term corrosion protection.

Zerust®/Excor® ActivPowder™(LS)-10F is a powerful ferrous corrosion inhibitor powder for challenging applications. The exceptionally fast diffusion rate of Zerust Activ™ inhibitors enables rapid delivery of protection, even in hard to reach spaces of structural voids, tubing and cavities. It also provides effective surface passivation to protect lightly contaminated metal surfaces from corrosion. Add ActivPowder™(LS) to voids to protect from corrosion after hydrostatic testing.

Apply powder by sprinkling or fogging into void spaces. To apply by spray, use a solution of powder dissolved in deionized water. Then, tightly seal the void or enclosure. At the end of its service life, ActivPowder™(LS)-10F powder may be removed or it may remain in the enclosure. The powder is water soluble and should be added to any standing water that cannot be removed in the enclosure. The ActivPowder™(LS) powder is a low odor and nitrite-free formula and has a REACH compliant Safety Data Sheet (SDS) available.

### Application Example

Protect hard to reach spaces with rapidly diffusing ActivPowder™(LS). It quickly reaches surfaces of internal spaces via its auto-fogging properties such as the inside of heat exchangers.



### ▶ Benefits

Fast-acting and effective on hard to reach surfaces

Safe\* and easy to use

Protects against flash corrosion

Does not cause hydrogen embrittlement

Protects against acid gases, salt air and other challenging contaminants

Powerful and long-lasting protection

### Application Type

Storage  
Shipping  
During Operation  
May be used with Zerust Packaging

\*Safe to use and handle. Product is not hazardous for people or the environment according to EU (CLP) or OSHA HazCom 2012 (US GHS).



Protect large void spaces of metals assets in storage and lay-up

## Specifications

<b>Product Information</b>	Zerust®/Excor® ActivPowder™(LS)-10F is a VCI (Vapor Corrosion Inhibitor) and FCI™ (Flash Corrosion Inhibitor) white powder.		
<b>Protected Metal Types</b>	Ferrous protection. Multimetal compatible. Do not place in direct contact with copper, brass or zinc. Test before use.		
<b>Properties</b>	pH	9 - 10.5	
	Solubility	> 25 g/L	

**Storage** Store tightly closed in original bag and box in a cool, dry place and away from sunlight for up to 2 years from the date of shipment. Store at or below 40% RH.

## Protection Capabilities\*

Zerust® Product Name	Normal Environment**		Aggressive Environment**	
	Volume of Protection (Up To)	Duration of Protection (Up To)	Volume of Protection (Up To)	Duration of Protection (Up To)
ActivTab™(LS)-25	0.25 ft³ (0.0071 m³)	6 months	0.025 ft³ (0.0007 m³)	15 days
ActivCapsule™ FAC1-1s	4 ft³ (0.12 m³)	1 year	0.35 ft³ (0.01 m³)	1 month
ActivPak®(LS)-35	35 ft³ (1 m³)	1 year	11 ft³ (0.3 m³)	2 months
ActivPak®-35	35 ft³ (1 m³)	2 years	11 ft³ (0.3 m³)	4 months
ActivPowder™(LS)-10F	1 lb = 280 ft³ (8 m³)	For years	1 lb = 90 ft³ (3 m³)	1 year
ActivPowder™-10F	1 lb = 280 ft³ (8 m³)	For years	1 lb = 90 ft³ (3 m³)	1 year

\* Protection ratings are based on the highest average tested protection properties and are not guaranteed. Results may vary according to usage environment and metal surface properties such as contaminants.

\*\* Normal environment (below 0.2 ppm SO<sub>2</sub>) defined as warehouses, light industrial areas, and shipping and storage in sealed packaging or enclosures. Aggressive environment (at or above 0.2 ppm SO<sub>2</sub>) defined as areas located in the vicinity of salts and acid gases such as oceans, petrochemical sites, wastewater treatment and pulp-paper plants or in enclosures that are not well sealed.

### DECLARATION

This Data sheet and information it contains is considered to be accurate at the date of printing. No representation or warranty, expressed or implied is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations.

### LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on validations and tests conducted by Northern Technologies International Corporation/Zerust® or its partners and are believed to be reliable, but the accuracy or completeness thereof is not guaranteed. We warrant our products will be free from defects when shipped to customer. Our obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Northern Technologies International Corporation/Zerust® or its partners or agent of the claimed defect within 3 months after shipment of product to customer. Customer shall pay all freight charges for replacement products. We shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. And any financial claims shall be limited to the value of the products sold.

Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of the company. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose. In no case shall Northern Technologies International Corporation/Zerust® be liable for incidental or consequential damages.

For full warranty and disclaimer information visit, [www.zerust.com/warranty](http://www.zerust.com/warranty).

©2013-2020 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor Tab®, EXCOR®, Flange Saver®, ICT®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST® 洁乐特 and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

## Availability

Zerust®/Excor® ActivPowder™(LS)-10F is stocked in boxes. Call to confirm. Additional quantities such as super sacks available upon request.

<b>ActivPowder™(LS)</b>	<b>Quantity</b>
460-F-00016	30 lb (14 kg)*
	* +/- 2% net weight

## Safety

- Safe to use and handle. Product is not hazardous for people or the environment according to EU (CLP) or OSHA HazCom 2012 (US GHS).
- Product in unopened original container prior to use does not meet criteria for hazardous waste according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).
- Product is nitrite-free. Manufactured on shared equipment that processes nitrites and may contain trace amounts.

A product of:  
Northern Technologies  
International Corp  
4201 Woodland Road  
Circle Pines, MN 55014  
USA

Phone: +1 763.225.6600  
Fax: +1 763.225.6645  
[sales@zerust.com](mailto:sales@zerust.com)  
[www.zerust.com](http://www.zerust.com)